

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/038176

International filing date: 15 November 2004 (15.11.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/520,277
Filing date: 13 November 2003 (13.11.2003)

Date of receipt at the International Bureau: 22 December 2004 (22.12.2004)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1261549

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

December 14, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A
FILING DATE.


APPLICATION NUMBER: 60/520,277
FILING DATE: November 13, 2003
RELATED PCT APPLICATION NUMBER: PCT/US04/38176

Certified by



Jon W Dudas

Acting Under Secretary of Commerce
for Intellectual Property
and Acting Director of the U.S.
Patent and Trademark Office

Please type a plus sign (+) inside this box → 

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE


PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. EV328618176US

PTO/SB/16 (02-01)
9703 U.S. PTO
60520277



INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
Gregg D.		Scheller		17820 Suzanne Ridge Drive, Glencoe, MO 63038	
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
ILLUMINATED LASER PROBE WITH ADJUSTABLE AREA OF ILLUMINATION					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number		021888			
OR Type Customer Number here					
<input checked="" type="checkbox"/> Firm or Individual Name		Joseph M. Rolnicki, Reg. No. 32,653			
Address		Thompson Coburn LLP			
Address		One US Bank Plaza			
City		St. Louis	State	MO	ZIP 63101-9928
Country		U.S.A.	Telephone	314-552-6286	Fax 314-552-7286
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		19	<input type="checkbox"/> CD(s), Number		
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets		4	<input type="checkbox"/> Other (specify)		
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE AMOUNT (\$)	
<input type="checkbox"/> Applicant claims large entity status					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:		20-0823		80.00	
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					

Respectfully submitted,

SIGNATURE Joseph M. Rolnicki

TYPED or PRINTED NAME Joseph M. Rolnicki

TELEPHONE 314-552-6286

Date 11/13/03

REGISTRATION NO.
(if appropriate)

32,653

Docket Number:

54084-44765

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

EXPRESS MAIL CERTIFICATE OF MAILING (37 CFR 1.10)
Express Mail No. EV328618176US

Docket No.
54084-44765

In Re Application Of:
Scheller, Gregg D.

Serial No.
Not Yet Assigned

Filing Date
Herewith

Examiner
Not Yet Assigned

Group Art Unit
Not Yet Assigned

Title:

ILLUMINATED LASER PROBE WITH ADJUSTABLE AREA OF ILLUMINATION

TO THE COMMISSIONER OF PATENTS AND TRADEMARKS

Transmitted herewith is:

- ☒ Transmittal Form for Provisional Patent Application
- ☒ Provisional Patent Application
- ☒ Drawings
- ☐ Power of Attorney: ☐ Executed ☐ Not Executed
- ☒ Postcard
- ☒ A copy of Transmittal for Deposit Account Processing of Filing Fee \$80.00 (Small Entity).


Signature


Dated: November 13, 2003

Joseph M. Rolnicki, Reg. No. 32,653
Thompson Coburn LLP
One US Bank Plaza
St. Louis, Missouri 63101-9928
314-552-6286
314-552-7286 FAX

Customer No. 021888

I certify that the document is being deposited on November 13, 2003 with the U.S. Postal Service as Express Mail under 37 C.F.R. 1.10 and is addressed to Mail Stop Provisional Application Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Express Mail No. EV328618176US


Signature of Person Mailing Correspondence

Joseph M. Rolnicki

Typed or Printed Name of Person Mailing Correspondence

P16B/REV01

Docket No. 54084-44765

PATENT

EXPRESS MAIL EV328618176US

**ILLUMINATED LASER PROBE WITH
ADJUSTABLE AREA OF ILLUMINATION**

Brief Description of the Drawing Figures

Features of the invention are set forth in the following detailed
5 description of the preferred embodiment of the invention and in the following
drawing figures wherein:

Figure 1 is a cross section of the surgical instrument of the invention
with a laser optic fiber of the instrument extended;

Figure 2 is a side view of the surgical instrument shown in Figure 1,
10 with the laser optic fiber retracted;

Figure 3 is an enlarged partial view of the portion of the instrument
shown in circle 3 of Figure 1;

Figure 4 is an enlarged partial view of the portion of the instrument
shown in circle 4 of Figure 1;

15 Figure 5 is a cross section of a further embodiment of the surgical
instrument of the invention with a laser optic fiber of the instrument extended;

Figure 6 is a side view of the surgical instrument shown in Figure 5, with the laser optic fiber retracted; and,

Figure 7 is an enlarged view of the cross section of the surgical instrument of Figure 5.

5

Detailed Description of a Preferred Embodiment

The surgical instrument of the invention is primarily intended to provide illumination light and laser light in laser eye surgery. However, the instrument may be used in other types of surgery. The instrument is designed as a
10 disposable instrument, but alternatively, the instrument could be a reusable instrument that is sterilized after each use.

The instrument has an elongate, narrow handle or hand piece 12 that has opposite proximal 14 and distal 16 ends. The handle 12 is dimensioned to a size similar to that of a pencil to fit comfortably in a surgeon's hand and
15 be easily manually manipulated by the surgeon's hand. A hollow interior bore 18 extends through the center of the handle 12 from the handle proximal end 14 to the handle distal end 16. A cavity 22 is recessed into a side of the handle. The cavity 22 intersects with the handle interior bore 18. The cavity 22 extends along a portion of the length of the handle 12 between a rearward
20 or proximal end 24 of the cavity and a forward or distal end 26 of the cavity.

An elongate, tubular tip 32 projects from the distal end 16 of the handle 12. The tubular tip 32 has an interior bore that extends through the tip from a proximal end 36 of the tip to a distal end 38 of the tip. As seen in Figures 1 and 2, the tip 32 has a bend 42 adjacent the tip distal end 38. In

alternative embodiments of the instrument, the tip 32 can be straight along its entire length. The tip proximal end 36 is received in the handle interior bore 18 at the handle distal end 16 and is secured stationary in place by adhesives or other equivalent means.

5 An elongate sleeve 44 is mounted in the handle interior bore 18 for reciprocating movement of the sleeve through the bore. The sleeve 44 has an interior bore 46 that extends through the sleeve from a proximal end 48 of the sleeve to a distal end 52 of the sleeve. As seen in Figures 1 and 3, a portion of the sleeve adjacent the sleeve distal end 52 is received in the
10 handle cavity 22 for reciprocating movement of this portion of the sleeve through the cavity.

 A finger tab 54 is positioned in the handle cavity 22 and is secured to the sleeve. The finger tab 54 has a shank portion 56 that extends into the handle cavity 22. The shank portion 56 has a transverse hole 58 extending
15 through a bottom portion of the shank portion. A portion of the sleeve 44 adjacent the sleeve distal end 52 extends through the transverse hole 58 of the finger tab 54. An internally threaded hole 62 extends downwardly through the finger tab shank portion 56. A set screw 64 is screw threaded into the internally threaded hole 62 and engages against a side of the sleeve 44 to
20 securely connect the finger tab 54 to the sleeve 44. A finger button 66 is provided at the top of the finger tab shank portion 56. The shank portion 56 positions the finger button 66 outwardly from the exterior surface of the handle 12 where the surgeon's hand holding the handle 12 can easily manipulate the finger button 66.

The finger tab 54 can be moved through the length of the handle cavity 22 between a rearward position of the finger tab where the finger tab is adjacent the cavity rearward end 24 as shown in Figure 2, and a forward position of the finger tab where the finger tab is positioned adjacent the cavity forward end 26 as shown in Figure 1. As the finger tab 54 is moved between the rearward and forward positions, the sleeve 44 is reciprocated in the handle interior bore 18 and in the cavity 22. The finger tab 54 moves the sleeve 44 toward the handle distal end 16 when the finger tab 54 is moved from the rearward position shown in Figure 2 toward the forward position shown in Figure 1. The finger tab 54 moves the sleeve 44 toward the handle proximal end 14 when the finger tab 54 is moved from the forward position shown in Figure 1 to the rearward position shown in Figure 2.

A laser optic fiber 72 having an elongate length with opposite proximal 74 and distal 76 ends extends through the handle 12, through the sleeve 44, and through the tip 32. A connector 78 is provided at the laser optic fiber proximal end 74. The connector 78 is adapted for connecting the laser optic fiber 72 to a separate laser light source to transmit laser light through the laser optic fiber to the laser optic fiber distal end 76. The laser optic fiber 72 extends through the handle interior bore 18, through the sleeve interior bore 46, and through the tip interior bore 34 to the laser optic fiber distal end 76 positioned adjacent the tip distal end 38.

A portion of the laser optic fiber 72 is secured to the interior of the sleeve 44 by an epoxy or other equivalent means. The remainder of the laser optic fiber 72 is free to reciprocate through the handle interior bore 18 and

through the tip interior bore 34 on movement of the finger tab 54 and the sleeve 44. When the finger tab 54 is moved to the rearward position shown in Figure 1, the laser optic fiber distal end 76 is positioned adjacent the tip distal end 38. When the finger tab 54 is moved toward the forward position as shown in Figure 1, a portion of the laser optic fiber adjacent the laser optic fiber distal end 76 is extended or projected from the tip distal end 38 as shown in Figure 1.

An illumination optic fiber 82 having a length with opposite proximal 84 and distal 86 ends extends through the handle 12, through the sleeve 44 and through the tip 32. The illumination optic fiber proximal end 84 is adapted to be connected to a separate illumination light source to transmit illumination light through the illumination optic fiber 82 to the illumination optic fiber distal end 86. The illumination optic fiber distal end 86 is positioned adjacent the tip distal end 38. The illumination optic fiber 82 is secured stationary in the interior of the tip 32 and in the interior of the handle 12 by adhesives or other equivalent means. A passage way 92 is provided through the adhesive in the sleeve 44 that secures the sleeve to the laser optic fiber 72. The illumination optic fiber 82 extends through the passageway 92, enabling the sleeve 44 and the laser optic fiber 72 to be reciprocated relative to the stationary illumination optic fiber 82 on manual manipulation of the finger tab 54.

In use of the surgical instrument, the laser optic fiber proximal end 74 is connected to a source of laser light and the illumination optic fiber proximal end 84 is connected to a source of illumination light. With the finger tab 54 in the rearward position shown in Figure 2, both the laser optic fiber distal end

76 and the illumination optic fiber distal end 86 are positioned inside the tip 32 adjacent the tip distal end 38.

The tip 32 is then inserted through a cannula positioned in an incision in the eye, or is inserted directly through the incision. The tip is positioned in the eye with the tip distal end 38 positioned relative to the surgical site to provide the desired area of illumination from the illumination light transmitted from the illumination optic fiber distal end 86. Moving the tip distal end 38 closer to the surgical site reduces the area illuminated by the illumination optic fiber 82. Pulling the tip distal end 38 back away from the surgical site expands the area of illumination by the illumination optic fiber 82.

With the desired area of the surgical site illuminated, the finger tab 54 can then be moved from its rearward position shown in Figure 2, toward the forward position shown in Figure 1. The finger pad is gradually manipulated by the hand of the surgeon, causing a portion of the laser optic fiber adjacent the laser optic fiber distal end 76 to be gradually extended from the tip distal end 38. This process is continued until the laser optic fiber distal end 76 is positioned at a desired position relative to the surgical site to begin the surgical procedure. When the surgical procedure is completed, the finger tab 54 is moved by the surgeon's hand to the rearward position of the finger tab. This retracts the portion of the laser optic fiber extended from the tip distal end 38 back into the tip 32. The tip 32 may then be removed from the eye.

Figures 5-7 show a further embodiment of the surgical instrument 102 of the invention. The surgical instrument 102 shown in Figures 5-7 is similar

to the surgical instrument of U.S. Patent No. 6,572,608 titled *Directional Laser Probe*, in that it is capable of directing laser light at a surgical site. In addition, the surgical instrument 102 of Figures 5-7 also provides a wide field of illumination at the surgical site.

5 The surgical instrument 102 is provided with an elongate, narrow handle or hand-piece 104 comprised of a forward piece 106 and a rearward piece 108. The forward piece 106 and rearward piece 108 are mounted to each other for relative rotation.

 The forward piece 106 has a length with opposite proximal 112 and
10 distal 114 ends. A center bore 116 extends through the forward piece between its proximal end 112 and its distal end 114. A cavity 118 is recessed into an exterior surface of the forward piece 106. The cavity 118 intersects with the center bore 116. The cavity 118 extends along a portion of the length of the forward piece 106 between a rearward or proximal end 122 of the cavity
15 and a forward or distal end 124 of the cavity.

 A tube 126 is secured in the forward piece center bore 116 at the forward piece proximal end 112. The tube 126 projects from the forward piece proximal end 112 to an annular stop 128 secured to an end of the tube. The tube 126 has a center bore 132 that is aligned with the handle forward
20 piece center bore 116.

 The handle rearward piece 108 has a length with opposite proximal 134 and distal 136 ends. A center bore 138 extends through the handle rearward piece 108. A portion of the rearward piece center bore 142 adjacent the rearward piece distal end 136 is enlarged and receives a portion of the

forward piece at the forward piece proximal end 112. The rearward piece center bore 138 is also formed with an annular groove 144 that receives the annular stop 128 of the handle forward piece tube 126. This mounts the handle forward piece 106 to the handle rearward piece 108 for relative rotation between the two pieces of the handle. The exterior surface of the handle rearward piece 108 is provided with a knurled ring 146 to facilitate manual rotation of the handle rearward piece 108 relative to the handle forward piece 106. The rearward piece center bore is provided with an additional enlarged portion 148 adjacent the rearward piece proximal end 134.

10 An elongate tubular tip 152 extends through a portion of the handle forward piece center bore 116 and cavity 118 and projects from the handle forward piece distal end 114. The tip 152 has a straight length that extends between opposite proximal 154 and distal 156 ends of the tip. A center bore 158 extends through the tip length. The tip 152 is received in the handle forward piece center bore 116 and in the handle cavity 118 for reciprocating movement of the tip 152 in the center bore 116 and cavity 118.

A tubular collar 162 is mounted on the exterior surface of the tip 152 adjacent the tip proximal end 154. The collar 162 has an annular groove 164 formed in the exterior surface of the collar. The tubular collar 162 reciprocates with the tip 152 in the handle forward piece center bore 116 and cavity 118.

A finger tab 166 is mounted on the tubular collar 162. The finger tab 166 has a shank 168 with a transverse hole 172 that receives the tubular collar 162. A finger button or finger pad 174 is provided at the top of the

shank 168. The shank 168 positions the finger pad 174 where it can be easily accessed by a finger of the surgeon's hand holding the handle 104 of the instrument. An internally threaded hole 176 extends through the shank 168 to the transverse hole 172. A set screw 178 is screw threaded into the internally threaded hole 176. The set screw 178 has a projection at its bottom that is received in sliding engagement in the tubular collar groove 164. The engagement of the set screw 178 in the collar groove 164 mounts the finger tab 166 to the tubular collar 162 for relative rotational movement between the tubular collar 162 and the finger tab 166. The engagement of the set screw 178 in the tubular collar groove 164 causes the tubular collar 162 and the tubular tip 152 to reciprocate through the handle forward piece cavity 118 and through the handle forward piece center bore 116 on reciprocating movement of the finger tab 166 in the cavity 118 between the cavity proximal end 122 and the cavity distal end 124.

A laser optic fiber 182 having an elongate length with opposite proximal 184 and distal 186 ends extends through the handle rearward piece center bore 138, through the handle forward piece center bore 116, and through the tubular tip 152.

A pair of diametrically opposed internally threaded tubes 188 extend into the enlarged portion of the handle rearward piece center bore 148 that is adjacent the handle rearward piece proximal end 148. The tubes 188 are positioned on opposite sides of the laser optic fiber 182. A pair of set screws 192 are screw threaded into the internally threaded tubes 188 and engage against opposite sides of the laser optic fiber 182, securing the laser optic

fiber stationary relative to the handle rearward piece 108. The set screws 192 prevent the laser optic fiber 182 from rotating relative to the handle rearward piece 108, and prevent the laser optic fiber 182 from moving through the center bore 138 of the handle rearward piece 108 and the center bore 116 of the handle forward piece 106.

With the finger tab 166 moved adjacent the cavity rearward or proximal end 122, the tubular tip 152 is moved to a retracted position relative to the instrument handle 104 and a distal end portion 194 of the laser optic fiber 182 projects from the tubular tip distal end 156. The laser optic fiber distal end portion 194 has a curved configuration as shown in Figures 5 and 7. In the preferred embodiment, a sleeve of a shape memory material 196, for example nitinol, is secured over the laser optic fiber distal end portion 194 to give this portion of the laser optic fiber its curved configuration. The laser optic fiber proximal end 184 is provided with a connector 198 that is adapted to connect the optic fiber to a laser light source for transmission of laser light through the length of the laser optic fiber 182 to the laser optic fiber distal end 186.

An elongate illumination optic fiber 202 having opposite proximal 206 and distal 208 ends extends through the handle rearward piece center bore 138, through the handle forward piece center bore 116, and through the tubular tip 152. The illumination optic fiber 202 is secured by adhesives or other equivalent means to the interior of the tubular tip 152. Thus, the illumination optic fiber 202 reciprocates through the handle rearward piece center bore 138 and the handle forward piece center bore 116 on movements of the finger tab 166 and the tubular tip 152 through the handle cavity 118.

Although a portion of the illumination optic fiber 202 is secured in the tubular tip 152, the portion of the laser optic fiber 182 that extends through the tubular tip 152 is free to slide through the length of the tubular tip 152 and is free to rotate in the tubular tip 152.

5 As seen in Figures 5-7, the illumination optic fiber distal end 208 has a tapered or conical configuration. This shape of the illumination optic fiber distal end 208 provides a wide field of illumination. The opposite proximal end 206 of the illumination optic fiber 202 is provided with a connector 212 that is adapted to connect to an illumination light source to transmit illumination light
10 through the length of the illumination optic fiber 202 to the illumination optic fiber distal end 208.

A sealing plug 214 is inserted into the enlarged portion 148 of the handle rearward piece center bore 138, closing this end of the bore.

A cylindrical cover 214 is assembled over the exterior surface of the
15 handle rearward piece 108, giving the handle an aesthetically pleasing appearance.

In use of the surgical instrument 102 of Figures 5-7, the laser optic fiber connector 198 is first connected to a laser light source and the illumination optic fiber connector 212 is connected to a source of illumination light. The
20 finger tab 166 is pushed to its forward position adjacent the cavity distal end 124 to cause the distal end portion 194 of the laser optic fiber 182 to be retracted into the tubular tip 152 as shown in Figure 6. The tip 152 is then inserted through a cannula positioned in an incision in the eye, or is inserted directly through the incision. The tubular tip distal end 156 and the

illumination optic fiber distal end 208 are positioned close to the desired surgical site, whereby the illumination light transmitted by the illumination optic fiber distal end 208 illuminates the surgical site.

The finger tab 166 is then gradually moved rearwardly toward the
5 cavity proximal end 122 causing the distal end portion of the laser optic fiber 194 to be gradually extended from the tip distal end 156. The handle forward piece 106 and handle rearward piece 108 can be rotated relative to each other to position the curvature of the laser optic fiber distal end portion 194 at a desired position of the surgeon relative to the surgical site. Once the proper
10 location of the laser optic fiber distal end 186 is achieved, laser energy can then be delivered to the surgical site of interest.

Retraction of the laser optic fiber distal end portion 194 is performed by pushing the finger tab 166 forward from its rearward position adjacent the cavity proximal end 122 toward the cavity distal end 124. This causes the
15 tubular tip 152 to straighten the laser optic fiber distal end portion 194 as it retracts the distal end portion into the tubular tip. With the laser optic fiber 182 contained in the tubular tip 152, the tip is then pulled back through the surgical entry site.

Thus, as discussed above, the surgical instruments of the present
20 invention provide a source of laser light for performing surgery and a source of illumination where the illuminated area of the surgical site can be adjusted, and where the direction of the laser light can be adjusted.

Although a specific embodiment of the invention has been described herein, it should be understood that other modifications and variations may be

made to the invention without departing from the intended scope of protection provided by the following claims.

What is claimed is:

- 1) A surgical instrument that provides both illumination light and laser light to a surgical site, the surgical instrument comprising:
 - a manually manipulatable handle;
 - 5 a tubular tip secured to the handle, the tip projecting from the handle to a distal end of the tip
 - an illumination optic fiber having a length with opposite proximal and distal ends, the illumination optic fiber extending through the handle and the tip to the illumination optic fiber distal end positioned adjacent the tip distal
 - 10 end, the illumination optic fiber being secured stationary relative to the tip;
 - a laser optic fiber having a length with opposite proximal and distal ends, the laser optic fiber extending through the handle and the tip to the laser optic fiber distal end positioned adjacent the tip distal end and the illumination optic fiber distal end; and,
 - 15 a mechanism on the handle, the mechanism being operatively connected to the laser optic fiber to move the laser optic fiber through the handle and the tip between a retracted position of the laser optic fiber where the laser optic fiber distal end is positioned adjacent the tip distal end and the illumination optic fiber distal end, and an extended position of the laser optic
 - 20 fiber where the laser optic fiber distal end is extended from the tip distal end and the illumination optic fiber distal end.

- 2) The surgical instrument of Claim 1, further comprising:
the illumination optic fiber having a tapered tip at the illumination
optic fiber distal end.
- 5 3) The surgical instrument of Claim 2, further comprising:
the illumination optic fiber tapered tip projecting outwardly from
the tip distal end.
- 10 4) The surgical instrument of Claim 2, further comprising:
the illumination optic fiber tapered tip having a conical
configuration.
- 15 5) The surgical instrument of Claim 1, further comprising:
a portion of the laser optic fiber adjacent the laser optic fiber
distal end having a curved configuration.
- 20 6) The surgical instrument of Claim 5, further comprising:
a curved sleeve is mounted on the laser optic fiber distal end
portion, and the curved sleeve holds the laser optic fiber distal end portion in
the curved configuration.

7) The surgical instrument of Claim 1, further comprising:

the handle having a forward piece and a rearward piece, the rearward piece being connected to the forward piece for relative rotation of the forward piece and the rearward piece;

5 the tip being mounted on the handle forward piece for relative movement of the tip and the handle forward piece; and,

the mechanism being on the handle forward piece.

8) The surgical instrument of Claim 7, further comprising:

10 the illumination optic fiber and the laser optic fiber are secured to the handle rearward piece for rotation of the illumination optic fiber and the laser optic fiber with the handle rearward piece relative to the handle forward piece and the tip.

15 9) A surgical instrument that provides both illumination light and laser light to a surgical site, the surgical instrument comprising:

an elongate handle having opposite proximal and distal ends, the handle having an interior bore with an interior surface extending through the handle from the handle proximal end to the handle distal end, and the
20 handle having an exterior surface with a cavity recessed into the exterior surface, the cavity intersecting the handle center bore and having opposite proximal and distal ends;

an elongate tubular tip having opposite proximal and distal ends, the tip having an interior bore with an interior surface extending through the tip

from the tip proximal end to the tip distal end, the tip proximal end being secured in the handle interior bore at the handle distal end;

an elongate sleeve having opposite proximal and distal ends, the sleeve having an interior bore that extends through the sleeve between the sleeve proximal and distal ends, the sleeve being mounted in the handle interior bore and in the handle cavity for reciprocating movement of that sleeve through the handle interior bore and the handle cavity;

a finger tab in the handle cavity and secured to the sleeve, the finger tab extending out of the handle cavity and beyond the handle exterior surface, the finger tab being movable in the handle cavity between a rearward position where the finger tab is adjacent the cavity proximal end, and a forward position where the finger tab is adjacent the cavity distal end, the finger tab moving the sleeve toward the handle distal end when the finger tab is moved from the rearward position to the forward position, and the finger tab moving the sleeve toward the handle proximal end when the finger tab is moved from the forward position to the rearward position;

an illumination optic fiber having a length with opposite proximal and distal ends, the illumination optic fiber proximal end being adapted to be attached to a separate illumination light source to transmit illumination light through the illumination optic fiber to the illumination optic fiber distal end, the illumination optic fiber extending through the handle interior bore, through the sleeve interior bore, and through the tip interior bore to the illumination optic fiber distal end positioned adjacent the tip distal end, the illumination optic fiber being secured stationary relative to the handle and the tip; and

a laser optic fiber having a length with opposite proximal and distal ends, the laser optic fiber proximal end being adapted to be attached to a separate laser light source to transmit laser light through the laser optic fiber to the laser optic fiber distal end, the laser optic fiber extending through the

5 handle interior bore, through the sleeve interior bore, and through the tip interior bore to the laser optic fiber distal end positioned adjacent the tip distal end when the finger tab is in the rearward position, the laser optic fiber being secured to the sleeve, and a portion of the laser optic fiber adjacent the laser optic fiber distal end being extended from the tip distal end when the finger

10 tab is moved from the rearward position toward the forward position.

10) The surgical instrument of Claim 9, further comprising:
the illumination optic fiber having a tapered tip at the illumination optic fiber distal end.

15



11) The surgical instrument of Claim 10, further comprising:
the illumination optic fiber tapered tip projecting outwardly from the tip distal end.

20 12) The surgical instrument of Claim 10, further comprising:
the illumination optic fiber tapered tip having a conical configuration.

- 13) The surgical instrument of Claim 9, further comprising:
a portion of the laser optic fiber adjacent the laser optic fiber
distal end having a curved configuration.
- 5 14) The surgical instrument of Claim 13, further comprising:
a curved sleeve is mounted on the laser optic fiber distal end
portion, and the curved sleeve holds the laser optic fiber distal end portion in
the curved configuration.
- 10 15) The surgical instrument of Claim 9, further comprising:
the handle having a forward piece and a rearward piece, the
rearward piece being connected to the forward piece for relative rotation
between the forward piece and the rearward piece;
the tip being mounted on the handle forward piece for relative
15 movement of the tip and the handle forward piece; and,
the finger tab and cavity being on the handle forward piece.
- 20 16) The surgical instrument of Claim 15, further comprising:
the illumination optic fiber and the laser optic fiber are secured
to the handle rearward piece for rotation of the illumination optic fiber and the
laser optic fiber with the handle rearward piece relative to the handle forward
piece and the tip.

Title: ILLUMINATED LASER PROBE WITH
ADJUSTABLE AREA OF ILLUMINATION
Inventor(s): Scheller, Gregg D.
Appl. No. EV328618176US
Docket # 54084-44765

1 / 4



Title:	ILLUMINATED LASER PROBE WITH ADJUSTABLE AREA OF ILLUMINATION
Inventor(s):	Scheller, Gregg D.
Appln. No.	EV328618176US
Docket #	54084-44765

2 / 4




Figure 3





Figure 4

Title: ILLUMINATED LASER PROBE WITH
ADJUSTABLE AREA OF ILLUMINATION
Inventor(s): Scheller, Gregg D.
Appln. No. EV328618176US
Docket # 54084-44765

3 / 4



ILLUMINATED LASER PROBE WITH ADJUSTABLE AREA OF ILLUMINATION

Scheller, Gregg D.

EV328618176US

54084-44765

4/4




Figure 7